



Technical Datasheet - Printed Vinyl Graphics

Vinyl - Gloss White

Face film: Calendered PVC
Thickness: 100 micron (0.1mm)
Tensile strength: 50N/25mm MD / 48N/25mm TD
Elongation at break: 180% MD
Adhesive type: Permanent solvent-free acrylic
Adhesive weight: 18gsm
Adhesion to glass 20 mins: 13N/25mm
Adhesion to glass 24 hours: 20N/25mm
Perceived tack: Medium
Application temperature: +8°C to +60°C
Service temperature: -20°C to +100°C
Backing paper weight: 140gsm
Shelf life: 1 year
Fire rating: Self-extinguishing
External weathering: 3 years

Vinyl - Matt White

Face film: Calendered PVC
Thickness: 100 micron (0.1mm)
Tensile strength: 50N/25mm MD / 48N/25mm TD
Elongation at break: 180% MD
Adhesive type: Permanent solvent-free acrylic
Adhesive weight: 18gsm
Adhesion to glass 20 mins: 13N/25mm
Adhesion to glass 24 hours: 20N/25mm
Perceived tack: Medium
Application temperature: +8°C to +60°C
Service temperature: -20°C to +100°C
Backing paper weight: 140gsm
Shelf life: 1 year
Fire rating: Self-extinguishing
External weathering: 3 years